



HOSPITAL OVERDOOR LIGHT ASSEMBLY

MODEL OD1-3-HOS



DESCRIPTION

Intended primarily for Hospital applications this simple yet effective and attractive 'Over Door Light' provides the capacity to illuminate up to three LED colours (typically Yellow, Red and Green) within a single standard mounting plate package .

Using latest LED technology, the light level is 'Super-Bright' but having low power consumption.

A Call-Point overdoor driver output can be reconfigured to drive a single LED or all LEDs simultaneously.

The display is available either in clear or frost acrylic.

Trigger output to either low or high switching is available via selectable jumper link and wiring installation is either by RJ45 or 4-way terminal block.

Part Numbers:

OD1-3-HOS-V(x) AH- for Active High, Clear Acrylic

OD1-3-HOS-V(x) AL- for Active Low, Clear Acrylic

OD1-3-HOS-(F)-V(x) AH- for Active High, Frost Acrylic

OD1-3-HOS-(F)-V(x) AL- for Active Low, Frost Acrylic

FEATURES & BENEFITS

- Clean & Smart Looking ODL
- Non-Obtrusive Design
- Bright & Easy to See
- High Refractive Prism – Clear or Frost
- 3 LED colour: Red, Green, Yellow
- Extra Long Life LED
- Low Power Consumption-Robust LED
- Dimensions equivalent to Clipsal 4000
- 118 mm (L) x 76 mm (W) x 13 mm (D)
- Input Supply: +12-27VDC
- Broad Viewing Angle: 120 degrees
- Wiring : RJ45 & Terminal Block
- Trigger Output: Selectable Low or High
- Optional: Buzzer

SPECIFICATIONS AND ILLUSTRATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Smart-Caller Pty Ltd

5/270 Lower Dandenong Rd, Mordialloc, VIC 3195, ABN. 14 217 255 933

P. (03) 9588 0833 F. (03) 9588 0933